

PRODUCT DATA

BIOSAN AQUA PLUS

DESCRIPTION

Bactericidal 2-component water dilutable epoxy coating.

MAIN PROPERTIES

Very hard - exceptional abrasion resistance - resistant to oils and solvents. Solvent free, almost odourless and easy to clean helps to maintain a hygienic environment.

RECOMMENDED USES

For the interior coating of walls and ceilings in areas where controlled hygienic conditions are of essential importance and where high abrasion resistance is needed.

TECHNICAL DATA

Appearance:	Semi-gloss (gloss 60°: ± 60%)
Colour:	White + mixing machine pastel colours
Density:	± 1,45 g/cm ³ (mixture)
Solids Content:	In volume: 48 - 50% In weight: 64 - 66%
Recommended film thickness:	Wet film: ± 140 micron (consumption: 7 m ² /l) Dry film: ± 70 micron (consumption: 7 m ² /l)
VOC-content:	0 g/l
Flashpoint:	Not flammable
Surface Spread of Flame:	Rated Class 0 to the UK Building Regulations (BS476 P6&7)

Drying times	20°C/50% r.h.
To touch:	3 hours
To recoat:	24 hours
Full hardness:	7 days

- Remarks:
- At lower temperatures (8 - 10°C), this product can only be recoated after ± 48 hours.
 - Potlife after mixing base and activator: 2 hours.

Coverage

Theoretical:	± 7 m ² /l per coat
Practical:	Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

SURFACE PREPARATION

The substrate should be dry and clean, free from ascending humidity and sufficiently coherent (tensile strength min. 6 kg/cm²).

Biosan Aqua Plus can be applied directly on most mineral substrates (f.i. old concrete, tiles, glass, etc.).

Curing compounds in case of poly-concrete have to be removed by means of grit blasting.

On new concrete or non-porous concrete, remove cement grout by grit blasting or treatment with Rust-Oleum Surfa Etch 108.

Porous substrates shall be impregnated with Biosan Aqua Plus diluted with 10 to 20% water.

Biosan Aqua Plus may not be applied on a flexible paint coat or a moving substrate.

DIRECTION FOR USE

To ensure homogeneity, coating materials should be thoroughly stirred prior to use.

Rust-Oleum Netherlands B.V.

Braak 1, 4704 RJ
P.O. Box 138, 4700 AC
Roosendaal, The Netherlands
T +31 (0)165 593 636
F +31 (0)165 593 600
info.nl@ro-m.com
www.ro-m.com

N.V. Martin Mathys S.A.

Kolenbergstraat 23
B - 3545 Zelem
Halen, Belgium
T +32 (0)13 460 200
F +32 (0)13 460 201
info.be@ro-m.com
www.ro-m.com

Rust-Oleum France S.A.S

11, Rue Jules Verne, B.P. 60039
95322 St-Leu-la-Forêt Cedex
France
T +33 (0)130 400 044
F +33 (0)130 409 980
info.fr@ro-m.com
www.ro-m.com

Rust-Oleum UK Ltd.

Unit 6, Spitfire Close
Coventry Business Park
Coventry, CV5 6UR
United Kingdom
T +44 (0)2476 717 329
F +44 (0)2476 718 930
info.uk@ro-m.com
www.ro-m.com

Rust-Oleum Mathys Italia s.r.l.

Largo Donegani 2
20121 Milano, Italia
T +39 335 10 93 482
info.it@ro-m.com
www.ro-m.com

PRODUCT DATA

BIOSAN AQUA PLUS

APPLICATION & THINNING

Brush/roller: Dilute 1st coat with max. 10% water.
Apply 2nd coat preferably undiluted.

Air-atomised spray: Not recommended.

Airless spray: Nozzle: 021 - 023 / Pressure: 220 bars.
1st coat: dilute with max. 10% water.
2nd coat: dilute with max. 5% water.

Cleanup: Water.

APPLICATION CONDITIONS

Minimum 8°C and maximum 80% R.H.

REMARKS

- In order to become a solid gloss finish, please respect the consumption quantities of the second layer, this means that a tin of 5 l has to be applied on a surface of approx. 35 m².
- Always provide good air ventilation; so even when it rains, windows and doors have to be opened wherever possible.
- The 2 components must be **mixed under mechanical agitation**.
- The use of Biosan products does not exclude the necessity to clean and disinfect on a normal and regular basis.

SAFETY

Consult Safety Data Sheet and Safety Information printed on the can.

SHELLIFE / STORAGE CONDITIONS

2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Rust-Oleum Netherlands B.V.

Braak 1, 4704 RJ
P.O. Box 138, 4700 AC
Roosendaal, The Netherlands
T +31 (0)165 593 636
F +31 (0)165 593 600
info.nl@ro-m.com
www.ro-m.com

N.V. Martin Mathys S.A.

Kolenbergstraat 23
B - 3545 Zelem
Halen, Belgium
T +32 (0)13 460 200
F +32 (0)13 460 201
info.be@ro-m.com
www.ro-m.com

Rust-Oleum France S.A.S

11, Rue Jules Verne, B.P. 60039
95322 St-Leu-la-Forêt Cedex
France
T +33 (0)130 400 044
F +33 (0)130 409 980
info.fr@ro-m.com
www.ro-m.com

Rust-Oleum UK Ltd.

Unit 6, Spitfire Close
Coventry Business Park
Coventry, CV5 6UR
United Kingdom
T +44 (0)2476 717 329
F +44 (0)2476 718 930
info.uk@ro-m.com
www.ro-m.com

Rust-Oleum Mathys Italia s.r.l.

Largo Donegani 2
20121 Milano, Italia
T +39 335 10 93 482
info.it@ro-m.com
www.ro-m.com