

## PRODUCT DATA

## SECCO SUPER

### DESCRIPTION

Water repellent product based on polysiloxanes.

### MAIN PROPERTIES

Water repellent - water vapour permeable (breathing) - colourless - does not change the colour of the substrate - may be applied on dry recent masonry.

### RECOMMENDED USES

Water repellent treatment of porous walls (bricks, concrete, cement, etc.).

### TECHNICAL DATA

Colour:	Colourless
Density:	± 0,8 g/cm <sup>3</sup>
Solids Content:	In volume: ± 5% In weight: ± 5%
VOC-content:	Max. 790 g/l
Flashpoint:	> 39°C

### Coverage

Theoretical:	1 - 4 m <sup>2</sup> /l
Practical:	Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

### SURFACE PREPARATION

Clean and dust off the outside walls that are sufficiently dry. Cracks and fissures must be filled up first.

### DIRECTION FOR USE

To ensure homogeneity, coating materials should be thoroughly stirred prior to use.

### APPLICATION & THINNING

Brush:	Apply undiluted until saturation (= wet outlook during a few seconds); it is advisable to apply a second coat within 15 minutes to obtain an optimum impregnation.
Roller:	Apply with woollen roller with long hairs. Do not dilute.
Air-atomised spray:	Not recommended. Can be flowed on the substrate with hand pressure equipment after removing the nozzle.
Airless spray:	Not recommended.
Cleanup:	White spirit.

### APPLICATION CONDITIONS

Dry weather, outside walls to be as dry as possible.

### REMARKS

- Non-porous surfaces (glass, blue stone, varnished brick, etc.) must be protected from spray mist or spatters of Secco.
- Apply Secco only on non-painted mineral or cement containing substrates. The substrate has to be porous.
- Can be recovered with Murfill or Paracem.

#### Rust-Oleum Netherlands B.V.

Braak 1, 4704 RJ  
P.O. Box 138, 4700 AC  
Roosendaal, The Netherlands  
T +31 (0)165 593 636  
F +31 (0)165 593 600  
[info.nl@ro-m.com](mailto:info.nl@ro-m.com)  
[www.ro-m.com](http://www.ro-m.com)

#### N.V. Martin Mathys S.A.

Kolenbergstraat 23  
B - 3545 Zelem  
Halen, Belgium  
T +32 (0)13 460 200  
F +32 (0)13 460 201  
[info.be@ro-m.com](mailto:info.be@ro-m.com)  
[www.ro-m.com](http://www.ro-m.com)

#### Rust-Oleum France S.A.S

11, Rue Jules Verne, B.P. 60039  
95322 St-Leu-la-Forêt Cedex  
France  
T +33 (0)130 400 044  
F +33 (0)130 409 980  
[info.fr@ro-m.com](mailto:info.fr@ro-m.com)  
[www.ro-m.com](http://www.ro-m.com)

#### Rust-Oleum UK Ltd.

Unit 6, Spitfire Close  
Coventry Business Park  
Coventry, CV5 6UR  
United Kingdom  
T +44 (0)2476 717 329  
F +44 (0)2476 718 930  
[info.uk@ro-m.com](mailto:info.uk@ro-m.com)  
[www.ro-m.com](http://www.ro-m.com)

#### Rust-Oleum Mathys Italia s.r.l.

Largo Donegani 2  
20121 Milano, Italia  
T +39 335 10 93 482  
[info.it@ro-m.com](mailto:info.it@ro-m.com)  
[www.ro-m.com](http://www.ro-m.com)

## PRODUCT DATA

## SECCO SUPER

### SAFETY

Consult Safety Data Sheet and Safety Information printed on the can.

### SHELLIFE / STORAGE CONDITIONS

2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

#### **Rust-Oleum Netherlands B.V.**

Braak 1, 4704 RJ  
P.O. Box 138, 4700 AC  
Roosendaal, The Netherlands  
T +31 (0)165 593 636  
F +31 (0)165 593 600  
*info.nl@ro-m.com*  
*www.ro-m.com*

#### **N.V. Martin Mathys S.A.**

Kolenbergstraat 23  
B - 3545 Zelem  
Halen, Belgium  
T +32 (0)13 460 200  
F +32 (0)13 460 201  
*info.be@ro-m.com*  
*www.ro-m.com*

#### **Rust-Oleum France S.A.S**

11, Rue Jules Verne, B.P. 60039  
95322 St-Leu-la-Forêt Cedex  
France  
T +33 (0)130 400 044  
F +33 (0)130 409 980  
*info.fr@ro-m.com*  
*www.ro-m.com*

#### **Rust-Oleum UK Ltd.**

Unit 6, Spitfire Close  
Coventry Business Park  
Coventry, CV5 6UR  
United Kingdom  
T +44 (0)2476 717 329  
F +44 (0)2476 718 930  
*info.uk@ro-m.com*  
*www.ro-m.com*

#### **Rust-Oleum Mathys Italia s.r.l.**

Largo Donegani 2  
20121 Milano, Italia  
T +39 335 10 93 482  
*info.it@ro-m.com*  
*www.ro-m.com*